



Pre-Press/Plates

Plate price includes:

- a) 1st data manipulation
- b) PDF / Good for printing
- c) 1 author correction (excluding proof)

Charged according to cost:

- a) DIN A4 colour proofs at 100.00 EUR
- b) Courier costs for sending proofs
- c) Additional author corrections

Prices valid/binding from camera-ready data**Camera-ready data:**

- Complete, modifiable final artwork data, prepared in standard programmes such as:
 - Adobe Illustrator
 - Adobe InDesign
 - ESKO PackEdge
 - ArtProIf you want your documents prepared in another programme please save the document as an uncompressed PDF file and also send us the images
- Editable texts including all the font sizes
- Logos and pictographs in vector format
- Used pixel images with at least 300dpi Resolution
 - leave all print layers and do not reduce them to a background layer. This leads to technical additional expenditure.
- A maximum of 8 colours per article may be created. Please note that opaque white and varnishes also correspond to one colour.

Template/Template (boards)

Please use only the template provided by Etimark AG for the design of your articles. Please contact us, we will be happy to supply you with the data for boards and labels.

Edge falling print

There are tolerances for punching, which are laminated with a bleed of 1.5 mm at a print with a falling edge. In further processing, the trim allowance is cut off. The bleed allowance should not be confused with the edge distance / safety distance.

Safety clearance

In order to ensure a clean print image and that no important elements are cut off during punching, a safety margin of 1 mm from the edge of the page should be maintained are held. Also avoid placing elements in the sealing edge area of blanks.

Refinements

Indicate which elements are to be refined (gold/silver, lacquer, embossing). White underlay – Indicate which elements must be underlaid with opaque white (this applies to circuit boards and transparent labels). If you do not specify anything for circuit boards, the entire lid is underlaid with white.

EAN code

Forward us your barcode requirements. If not specified, we will follow the industry standard.

LMIV (Food Information Regulation)

Please note that according to LMIV the x-height of the font must be at least 1.2 mm to ensure good legibility. For packaging or containers whose largest surface area is less than 80 cm², the x-height of the font size is at least 0.9 mm.

Further remarks:

- Offset proofs are simulated with a white, coated paper type according to the Process Standard Print. Due to the physical properties of the substrate aluminium (grey surface), particularly light colour tones can only be reproduced to a limited extent. For an optimal adaptation (within the limits of what is possible) we ask you to send us a colour sample as soon as possible.
- Flexotechnical and in-house adjustments to the data must always be made by Etimark AG.
- The goods produced by Etimark AG for printing is to be checked and signed by the customer and returned.